ATTACHMENT



FILTER BOXES

Case 1:03-cv-00355-SJM-SPB Document 48-26 Filed 02/16/2003 0 PENG RADIAL TYPE P

INDUSTRIAL EXHAUSTERS
Arrangement 1

	, A	NAT' VA	715/339-3024				, Atti	នាម្ដេចពេចកេ		
`		TOMER:	Underwood Air Systems,			(1. 1.2.) (1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	ROTATION DISCHARGE POSITIONS Clockwise sho			
	ITEM NO.	QUAN.	·	DATE	SALES OFFICE		<u>·</u>	CIUCKWISE SILO		
			CUSTOMER P.O./JOB#							
	1	2	VWA0870 / 890843	UAS POCITION	ROTATION (viewe	d from drive side)	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			
			FAN BLOWER SIZE SWS! EXTRA HEAVY HD DUTY		STD SPEC CLOCKWISE COUNTERCLOCKY			Up Blast		
			37		UB DENSITY	1 X TEMPERATURE	1 M MAX OPERATING	CW 360		
			CFM S.P. PERFORMAI	NUE DIT		·	TEMPERATURE			
			34,000		Std.	Std. PECIAL INSTRUCTIONS	S	((<u>(</u> @_())		
	YES		ACCESSURIES							
	П	ACCESS			<u> </u>	•	88	Top Angular Ui CW 45		
							7			
	_	<u>drain Pl</u>			වු		SE	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
		<u>SPLIT_HC</u>	OUSING SPLIT BOX FLANGED DRILL SCREEN BOX				년 '	Top Horizontal		
		INLEI		H1.00	 NSTRI	Inc. WISCONSIN	ATE	CM 90		
	П	INLET_VA	EXTERNAL		Z	Z				
	-		DRILL			ပ္သည္ဟ		(<u>^</u>		
ς.		FLANGED	PARALLEL OPPOSED INLET OUTLET	MANUAL AUTO	U	A KIN	E	Top Angular Do		
)		DAMPER			Œ		1/2	CW 135		
	M	PAINI	X		C	IAF LIPS,				
	_	GUARDS	SHAFT BELT COUPLING							
					<u> </u>	m ()	E C	Down Blast		
		PLUG_CC	OLER				10	CW 180		
		SHAFT_C	OOLING WHEEL STANDARD GAS TIGHT							
	Г٦	SHAFT S				–				
			TYPE A B C)		Y Y		
	L	SPAHK_I	AIS SPRING	W X Y				Bottom Angular Do CW 225		
		INTERGAL	BASE MOTOR POSITION			N.A				
		MOTOR	SUPPLIED BY: IAP 🔲 OTHERS	□						
			MOUNTED BY: 1AP OTHERS	BY: JAP OTHERS -				1 4		
			MODITIES ST. TITLE				r ♥ 1	Bottom Horizon CW 270		
			HP RPM DUTY ENCL	FRAME						
		DRIVE	V-BELT C.S. ADJ							
	С	SILENCE	INLET OUTLET R		All dr	awings are	the The			
)			•	prope	property of IAP, Inc., and				
مهد		TRANSIT	ONS		any us	se for manu	racturing	CW 315		
		ROTABLE	HOUSINGS			ses is strict den.	IAP, Inc.	FORM RP-1		
		المعتب المعدمة								

Dov



CP0355-SJM-SPB SUBMITTEAL DATA 16/2006

3	X	0	PE.	3 0	AB	ΙAΙ
		T	PE.	Р		

INDUSTRIAL EXHAUSTERS

									Arrangement
1	TOMER:		l Air Syster	ns, Inc.	. •				ROTATION DISCHARGI POSITIONS (Clockwise sho
110.		CUSTOMER	P.O./JOB#	DATE	SALES	OFFICE	Sept 24	•	T T
1	2	VWA0870 /	890843	9/11/89	UAS	3			4.0
		FAN BLOWER SIZE	SWSI	EXTRA HEAVY		AGE POSITION		viewed from drive side) COUNTERCLOCKWISE	
•		37	X	HD DUTY	STO	SPEC 7: UB 🔲	1	1	Up Blast CW 360
		CFM		RMANCE BHP		DENSITY	TEMPERATURE	MAX OPERATION TEMPERATUR	4G
		34,000				Std.	Std.		
YES						SI			
□ a	BOLTED HINGED RAISED ACCESS DOOR					Z	Top Angular U		
	DAIN PII	ıc				H		11 1989	CW 45
	DRAIN PLUG					5	. <i>'</i>	SEP	
LJ S	PLIT HOL		SPLIT BOX Screen box	· · · · · · · · · · · · · · · · · · ·		Ď	•	1	1 XX
□ 11					,,,	旹	E	H	Top Horizontal CW 90
4	EXTERNAL INLET VANE					Z	SN(ATE	
™ Fi	DRILL FLANGED OUTLET					Ö	Inc. WISCONSIN	\mapsto	
5	PARALLEL OPPOSED INLET OUTLET MANUAL AUTO					Ŭ	Inc	8	
/ 🗆 D	AMPER	STANDARD HI-TEN	AP OTHER			Œ	G, W	Ch.	Top Angular Dov CW 135
X P/		X D	OUPLING	<u> </u>		G		\mathcal{L}	
🗀 🗓	JARDS	SHAFT BELT C		·				7	(A)
. □ PI	UG COOL	ER		*		囯	10 Pi	13	
- -						巨		10	Down Blast CW 180
L. St	AFT COU	LING WHEEL STANDARD	GAS TIGH	Ţ		<u></u> i			
☐ SH	AFT SEA	LS 🗍 TYPE A	₿ □_					h	
□ <u>se</u>	ARK RES	ISTANCE		J		O			N Y
	ERGAL B	RIS SPRING	i Motor pösitii	Y X Y	Z 			And the second	Bottom Angular Dov CW 225
			•			`` `			
<u> </u>	TOR	SUPPLIED BY: IAP	OTHERS	· L		ا ہے ۔		ر الم	(a)
		MOUNTED BY: IAP	OTHERS		· ·			n H	100
				. .	£ +		u V		Bottom Horizont CW 270
☐ DRI	VF	HP RPM DU V-BELT ☐ C.S. [FRAME		<u>L</u>	<u></u>		
		INLET OUTLE		•	 .		•		
្ត 🗆 នារា	NCER			s			vings are		
J ☐ IBA	NSITIONS	<u> </u>						Inc., and	Bottom Angular (CW 315
☐ ROTA	ABLE HO	USINGS	·	\(\frac{1}{2} \)			s is strict	ufacturing. Iv	l
						forbidde		IAP, Inc.	FORM RP-1
	ER BOXES	<u> </u>							